

MIL-STD-188-182
18 SEPTEMBER 1992

MILITARY STANDARD

INTEROPERABILITY STANDARD

FOR

5-kHz UHF DAMA TERMINAL WAVEFORM



DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

(This page intentionally left blank.)

MIL-STD-188-182

FOREWORD

1. Originally, Military Standard -188 (MIL-STD-188) covered technical standards for tactical and long-haul communications. It later evolved through revisions (MIL-STD-188A, MIL-STD-188B) into a document applicable to tactical communications only (MIL-STD-188C).

2. The Defense Communications Agency (DCA), now the Defense Information Systems Agency (DISA), published DCA circulars (DCAC). These DCACs promulgated standards and engineering criteria that apply to the long-haul Defense Communications System (DCS) and to the technical support of the National Military Command System (NMCS).

3. As a result of a Joint Chiefs of Staff (JCS) action, standards for all military communications are now being published in a MIL-STD-188 series. The MIL-STD-188 series is subdivided into a MIL-STD-188-100 series, which covers common standards for tactical and long-haul communications; a MIL-STD-188-200 series, which covers standards for tactical communications only; and a MIL-STD-188-300 series, which covers standards for long-haul communications only. Ultimately, the -200 and -300 series will be absorbed into the -100 series.

4. This MIL-STD was prepared to comply with Joint Staff direction requiring that a new standard be developed. This standard defines all technical characteristics essential for interoperability and performance of satellite communications (SATCOM) terminals using 5-kHz ultra high frequency (UHF) demand-assigned multiple access (DAMA) SATCOM transponder channels. This MIL-STD defines mandatory system parameters for planning, engineering, procuring, and using UHF SATCOM terminals in joint operations.

5. This MIL-STD is approved and mandatory for use by the Office of the Secretary of Defense, the military departments, the JCS, the unified and specified commands, Department of Defense (DoD) agencies, and DoD field activities. It ensures interoperability and compatibility in accordance with DoD Instruction 5000.2, dated 23 February 1991.

6. Beneficial comments (recommendations, additions, deletions) and any pertinent data that may be of use in improving this MIL-STD should be addressed to:

Director
Joint Interoperability and Engineering Organization
ATTN: TBBA
Fort Monmouth, NJ 07703-5613

by using the self-addressed Standardization Document Improvement Proposal form (DD Form 1426) appearing at the end of this MIL-STD or by letter.

(This page intentionally left blank.)

MIL-STD-188-182

CONTENTS

<u>PARAGRAPH</u>		<u>PAGE</u>
1.	SCOPE	1
1.1	Purpose	1
1.2	Scope	1
1.3	Application guidance	1
2.	APPLICABLE DOCUMENTS	3
2.1	Government documents	3
2.2	Specifications	3
2.3	Order of precedence	4
3.	DEFINITIONS	5
3.1	Acronyms used in this MIL-STD	5
3.2	Definitions of terms	8
4.	GENERAL REQUIREMENTS	15
4.1	Communications system characteristics	15
4.2	Waveform description	15
4.2.1	General waveform structure	16
4.2.1.1	Waveform segment description	16
4.2.1.1.1	Forward orderwire segment	16
4.2.1.1.2	Return orderwire segment	19
4.2.1.1.2.1	Return orderwire message time-slots	19
4.2.1.1.2.2	Return orderwire ranging time-slots	19
4.2.1.1.3	Communications segment	19
4.2.2	Error control	19
4.2.2.1	Error detection	19
4.2.2.2	Error correction	19
4.2.2.3	Interleaving/deinterleaving	19
4.2.3	Modulation	19
4.2.3.1	Modulation format	19
4.2.3.2	Modulation rates	21
4.3	Terminal performance requirements	21
4.3.1	Uplink frequency accuracy	21
4.3.2	Terminal duplex	21
4.4	Communications options	22
4.5	Security characteristics	22
5.	DETAILED REQUIREMENTS	27
5.1	Waveform requirements	27
5.1.1	Forward orderwire segment and time-slot fields	27
5.1.2	Return orderwire segment	32
5.1.2.1	ROW Ranging time-slot fields	36
5.1.2.2	ROW message time-slot fields	36
5.1.3	Communications segment	38

5.1.3.1	Communications circuit-service time-slot fields	38
---------	--	----

CONTENTS

<u>PARAGRAPH</u>		<u>PAGE</u>
5.1.3.2	Communications message-service time-slot fields	40
5.1.4	Data field transmission	40
5.1.5	System guard time	40
5.2	Synchronization	43
5.2.1	Downlink synchronization	43
5.2.2	Uplink synchronization	44
5.2.2.1	Terminal active ranging	44
5.2.2.1.1	Terminal contention ranging	44
5.2.2.1.2	Contention-ranging backoff algorithm . . .	44
5.2.2.1.3	Terminal assigned ranging	45
5.2.2.2	Terminal passive ranging	45
5.3	Link quality measurement	46
5.4	Communications characteristics	46
5.4.1	Communications services	46
5.4.1.1	TDMA communications services	46
5.4.1.1.1	Circuit service	47
5.4.1.1.2	Message service	47
5.4.1.2	Dedicated communications services	47
5.4.1.3	25-kHz TDMA communication services	47
5.4.2	Communications Protocols	48
5.4.2.1	TDMA access control	48
5.4.2.1.1	Preassignment of circuit services	48
5.4.2.1.2	Precedence and preemption	49
5.4.2.1.3	Access restrictions	49
5.4.2.1.3.1	Terminal access restriction	49
5.4.2.1.3.2	System access restriction	49
5.4.2.1.3.3	System service restriction	49
5.4.2.1.4	Authorization	50
5.4.2.1.5	Network login	50
5.4.2.1.5.1	Terminal login	50
5.4.2.1.5.2	Orderwire message acknowledgement	50
5.4.2.1.5.2.1	FOW message acknowledgment	50
5.4.2.1.5.2.2	ROW message acknowledgment	50
5.4.2.1.6	Network management	50
5.4.2.1.6.1	Terminal logout	50
5.4.2.1.6.2	Automatic logout	51
5.4.2.1.6.3	Queued service requests	51
5.4.2.1.6.4	Queued maintenance	51
5.4.2.1.7	Frame construction	52
5.4.2.1.7.1	Forward orderwire resource assignment . .	52
5.4.2.1.7.2	Communications service assignment	52
5.4.2.1.7.3	Return orderwire resource assignment . . .	52
5.4.2.1.7.4	Protocol for contention return orderwire message transmission	53

5.4.2.1.7.4.1	Initial transmission of contention return orderwire message	53
---------------	--	----

CONTENTS

<u>PARAGRAPH</u>		<u>PAGE</u>
5.4.2.1.7.4.2	Return orderwire acknowledgment/retry protocol	53
5.4.2.1.7.5	Contention reporting	54
5.4.2.2	TDMA circuit service	54
5.4.2.2.1	Circuit service setup	54
5.4.2.2.2	Circuit service management	54
5.4.2.2.3	Buffer requirements imposed by clock differences	55
5.4.2.2.4	Circuit burst format for synchronous communications	55
5.4.2.2.5	Circuit burst format for asynchronous communications	58
5.4.2.2.6	Circuit service teardown	58
5.4.2.3	TDMA message service	60
5.4.2.3.1	Message service setup	60
5.4.2.3.2	Message service management	60
5.4.2.3.2.1	Block status polling	60
5.4.2.3.2.2	Block acknowledgments	61
5.4.2.3.2.3	Point-to-point message processing	61
5.4.2.3.2.4	Subnet message processing	61
5.4.2.3.2.5	Unused-byte counter	61
5.4.2.3.2.6	Message acknowledgment	62
5.4.2.3.3	Message service teardown	62
5.4.2.3.4	Terminal busy status	63
5.4.2.4	Dedicated channel service	63
5.4.2.4.1	Terminal requirements	63
5.4.2.4.2	Protocol	63
5.4.2.5	Network management	64
5.4.2.5.1	Addressing	64
5.4.2.5.1.1	Node address	64
5.4.2.5.1.2	Reserved address	65
5.4.2.5.1.3	Demarcation of subnet addresses	65
5.4.2.5.2	Address guard lists	64
5.4.2.5.3	Service requests and time-slot assignments	66
5.4.2.5.4	Network transition	67
5.4.2.5.4.1	PCC transition	67
5.4.2.5.4.2	Channel transition	68
5.4.2.5.5	Status report	68
5.4.2.5.6	TDMA service teardown	68
5.4.2.5.6.1	Service teardown request	68
5.4.2.5.6.1.1	Circuit service	68
5.4.2.5.6.1.1.1	Active circuit service	68
5.4.2.5.6.1.1.2	Queued circuit service	68
5.4.2.5.6.1.2	Message service	68
5.4.2.5.6.1.2.1	Active message service	68
5.4.2.5.6.1.2.2	Queued message service	68

MIL-STD-188-182

5.4.2.5.6.2	Service teardown protocol	68
5.4.2.5.6.2.1	Circuit service	68
5.4.2.5.6.2.1.1	Active circuit service	68

CONTENTS

<u>PARAGRAPH</u>		<u>PAGE</u>
5.4.2.5.6.2.1.2	Queued circuit services	69
5.4.2.5.6.2.2	Message service	69
5.4.2.5.6.2.2.1	Active message service	69
5.4.2.5.6.2.2.2	Queued message service	69
5.4.3	Error control	69
5.4.3.1	Error detection	69
5.4.3.2	Error correction encoding/decoding	70
5.4.3.3	Interleaving/deinterleaving	72
5.4.4	Modulation requirements	72
5.4.4.1	Modulation formats	72
5.4.4.2	Modulation rates	77
5.4.4.3	Adjacent channel emissions	77
5.5	Security characteristics	77
5.5.1	Orderwire encryption/decryption	77
5.5.1.1	TRANSEC key selection	77
5.5.1.3	Encryption of the FOW	79
5.5.1.4	Decryption of the FOW	79
5.5.1.5	Encryption of the ROW	80
5.5.1.6	Decryption of the ROW	80
5.5.2	User data encryption/decryption	81
5.5.2.1	Voice security	81
5.5.2.2	Data security	81
5.6	Multiple channel network operations	81
5.6.1	Channel reassignment (TDMA)	81
5.6.2	Timed channel assignment (dedicated)	82
6.	NOTES	83
6.1	Communications Scenarios	83
6.2	Communications time-slot assignment example	87
6.3	ROW time-slot assignment example	90
6.4	Contention ROW segment size determination example	94
6.5	Tailoring guidance	94
6.6	Key word listing	94

<u>FIGURE</u>		<u>PAGE</u>
1	Frame format	17
2	FOW slot field definitions	28
3	ROW ranging field definition	34
4	ROW message field definitions	35
5	Communications circuit-service field definitions	39
6	Communications message-service field definitions	41
7	Allocated guard times for bursts	42

8	Circuit-service communications field formats for synchronous communications	57
---	--	----

MIL-STD-188-182

CONTENTS

<u>FIGURE</u>		<u>PAGE</u>
9	Circuit-service field formats for asynchronous communications	59
10	Rate - 1/2 convolutional encoder	71
11	Example input to the modulator	76
12	Time Slot Number (TSN) Format	78
13	Communications scenarios and equipment locations	84
14	FOW communications assignment messages	89
15	Starting location for communications time slots .	91
16	FOW messages transmitted by PCC	92
17	ROW slot assignments	93
18	Contention ROW segment size determination	95

<u>TABLE</u>		<u>PAGE</u>
I	FOW directed messages	18
II	ROW messages	20
III	Modulation rates	21
IV	Circuit-service communications options	23
V	Message-service communications options	25
VI	Burst preamble characteristics	29
VII	Start-of-message sequence	29
VIII	Burst type field	30
IX	Contention ranging slot field	31
X	FOW directed messages and required responses . .	33
XI	ROW messages and FOW responses	37
XII	Communications services	46
XIII	Network circuit communications I/O data rates . .	47
XIV	Size of the data field for circuit communications	55
XV	Address guard-list contents	65
XVI	Interleaver sequence--block 1	73
XVII	Interleaver sequence--block 2	74
XVIII	Allowable adjacent channel emissions, narrowband	77

<u>APPENDIX</u>		<u>PAGE</u>
APPENDIX A	FOW SYSTEM MESSAGES	97
APPENDIX B	FOW DIRECTED MESSAGES	99
APPENDIX C	ROW MESSAGES	137
APPENDIX D	FREQUENCY PLANS	173

(This page intentionally left blank.)

MIL-STD-188-182